



RIO | oslo

CABO
8/14W LED

FL3



INTERNAL DMX

CABO FL3 :

The CABO FL3 Series of LED Underwater Recessed fixtures are perfect for any submersible lighting application. Great for pool or pond illumination as well as fountain and waterfall lighting. Comes with optional PVC mounting sleeve.

- 5-year warranty
- Long life : 30,000 hours | Power Factor : >0.9
- Internal integrated DMX for easy wiring and installation


SPECIFICATIONS

Housing & Trim Ring	Stainless steel
Cable Gland	IP68
Environment	up to 5m depth
Driver	Single color —1 circuit RGB 3in1 —3 circuits
Cord	OSLO Warm White —(1)6ft RIO RGB —(2)6ft
Cord Termination	OSLO Warm White —(1)Tinned wire ends RIO RGB —(2)Tinned wire ends


PHOTOMETRICS

Intensity (foot candles) **8w / 25°**
30 Degree Beam
Warm White

Height		ø(m)
1m	168	0.27m
2m	41.8	0.62m
3m	18.6	0.83m
4m	10.5	1.11m
6m	4.6	1.66m



DIMENSIONS



Model Number	LED Array	Input Voltage	Color	Beam Angle*	Cord Termination	Max Power	LUM Flux
FL3-L16-1AWB-S-20HW	1 x 6W	12VAC	Warm White 3000K	25°	2-wire	3W	810
FL3-L16-1ACB-S-20HW	1 x 6W	12VAC	Cool White 6000K	25°	2-wire	3W	990
FL3-L26-2DXB-S-20HW	2 x 6W	24VDC	RGB	25°	(2) 2-wire	18.2W	Variable
FL3-L26-1AWC-S-20HW	2 x 6W	12VAC	Warm White 3000K	25°	2-wire	7W	1606
FL3-L26-1ACC-S-20HW	2 x 6W	12VAC	Cool White 6000K	25°	2-wire	7W	1890

*Also available in 15°, and 40°
Inquire for more information



illuminfx

illuminfx reserves the right to make changes to specifications at any time with or without notice

cabo FL3 2015 | © 2015 illuminfx
www.illuminfx.com | 585 - 254 - 8010