



RIO | oslo

CABO
8/14W LED

FL3



INTERNAL DMX

CABO FL3 :

The CABO FL3 Series of LED Underwater Recessed fixtures are perfect for any submersible lighting application. Great for pool or pond illumination as well as fountain and waterfall lighting. Comes with optional PVC mounting sleeve.

- 5-year warranty
- Long life : 30,000 hours | Power Factor : >0.9
- Internal integrated DMX for easy wiring and installation


SPECIFICATIONS

| | |
|---------------------|--|
| Housing & Trim Ring | Stainless steel |
| Cable Gland | IP68 |
| Environment | up to 5m depth |
| Driver | Single color —1 circuit RGB 3in1 —3 circuits |
| Cord | OSLO Warm White —(1)6ft RIO RGB —(2)6ft |
| Cord Termination | OSLO Warm White —(1)Tinned wire ends RIO RGB —(2)Tinned wire ends |


PHOTOMETRICS

Intensity (foot candles) **8w / 25°**
30 Degree Beam
Warm White

| Height | | ø(m) |
|--------|------|-------|
| 1m | 168 | 0.27m |
| 2m | 41.8 | 0.62m |
| 3m | 18.6 | 0.83m |
| 4m | 10.5 | 1.11m |
| 6m | 4.6 | 1.66m |



DIMENSIONS



| Model Number | LED Array | Input Voltage | Color | Beam Angle* | Cord Termination | Max Power | LUM Flux |
|---------------------|-----------|---------------|---------------------|-------------|------------------|-----------|----------|
| FL3-L16-1AWB-S-20HW | 1 x 6W | 12VAC | Warm White 3000K | 25° | 2-wire | 3W | 810 |
| FL3-L16-1ACB-S-20HW | 1 x 6W | 12VAC | Cool White 6000K | 25° | 2-wire | 3W | 990 |
| FL3-L26-2DXB-S-20HW | 2 x 6W | 24VDC | RGB | 25° | (2) 2-wire | 18.2W | Variable |
| FL3-L26-1AWC-S-20HW | 2 x 6W | 12VAC | Warm White 3000K | 25° | 2-wire | 7W | 1606 |
| FL3-L26-1ACC-S-20HW | 2 x 6W | 12VAC | Cool White 6000K | 25° | 2-wire | 7W | 1890 |

*Also available in 15°, and 40°
Inquire for more information



illuminfx

illuminfx reserves the right to make changes to specifications at any time with or without notice

cabo FL3 2015 | © 2015 illuminfx
www.illuminfx.com | 585 - 254 - 8010