



SPECTRUM SELECT

Full DMX Control

SS



SPECTRUM SELECT

The Spectrum Select SS-303 DMX Controller had been designed to offer the perfect lighting control solution for almost any environment. A DMX signal is sent from the controller to either DMX Decoders or Smart DMX Fixtures offered by IlluminFx. You can control each fixture independently or together, and program almost any lighting program you can imagine with the ESA Pro Software.

SS-303 Wall Panel

The touch sensitive wall panel controller allows for easy on the fly adjustment of the lighting system connected to the SS-303. You can easily cycle through programs, adjust speed, and brightness, and even choose the color of the lighting system.



SPECIFICATIONS

Voltage	6VDC 0.6A or POE
DMX 512 (x2)	128 to 1024 DMX channels
Computer Access	Mini USB
WiFi Control	iPhone, Android, and Tablet support
Other Ports	RS232, Clock, 8 dry contact ports, 5V Ouput relay
Memory	microSD card
Working Temp	14°F-113°F
Mounting	Standard single or double gang box
Dimensions	146 x 106 x 11mm
Weight	247g
Standards	EC, EMC, ROHS, ETL

WiFi Control

With the Spectrum Select system, you can also control your lights from you smartphone or tablet with the free and intuitive Easy Remote app.

