#### in grade



## RoHS C C C Compliant

Mounting Sleeve included with each IG2

# CASPER IG2 :

The CASPER IG2 Series of LED In Grade fixtures are perfect for any hardscape illumination application. This compact, yet powerful 3W fixture is great for retaining walls, columns, and even small plants. Comes with optional PVC mounting sleeve.

3w / 30°

0.9m

1.8m

2.7m

3.6m

4.5m

Н

۷

0.9m

1.8m

2.7m

3.6m

4.5m

V Spread : 25.4m

H Spread : 25.4m

Intensity (foot candles)

Asymmetrical Beam Warm White

4.5

1.15

0.51

0.29

0.16

2m

4m

6m

8m

10m

Height

- 5-year warranty
- Long life : 50,000 hours

PHOTOMETRICS

Intensity (foot candles)

30 Degree Beam Warm White

7.6

2.0

0.84

0.41

0.31

2m

4m

6m

8m

10m

Height

### RIO | oslo CASPER 3W LED

IG2

### SPECIFICATIONS

Housing	Die cast aluminum, gray powder coat			
Trim Ring	316 <sup>#</sup> stainless steel			
Glass	Step-tempered clear glass T=7mm			
Loading Capacity	Exert force of $\emptyset^{2/5}$ =1362 pounds			
Lens	Optical lens efficiency ≥85%			
Cable Gland	IP68 PG-9 copper and nickel coated			
Waterproof Seal	Molded shaped double silicone seal			
LED	<u>TO</u> power type			
Driver	Single color—1 circuit RGB 3in1—3 circuits			
Cord	6 ft			
Cord Termination	OSLO Warm White—Tinned wire ends RIO RGB—Male IP68 Quick-Connect			
Mounting Sleeve	011 PVC			

#### DIMENSIONS



Model Number	LED Array	Input Voltage	Color	Beam Angle	Cord Termination	Max Power	LUM Flux
IG2-L13-1AWC-S-06HW	1 x 3W	12VAC	Warm White 3000K	30°	2-wire	2.5W	65
IG2-L13-1AWW-S-06HW	1 x 3W	12VAC	Warm White 3000K	ASY 45°x35°	2-wire	2.5W	65
IG2-L13-2DXC-S-061M	1 x 3W	24VDC	RGB	30°	Male QC Plug	3.5W	Variable
IG2-L13-2DXW-S-061M	1 x 3W	24VDC	RGB	ASY 45°x35°	Male QC Plug	3.5W	Variable

3w / 45°x30°

Н

0.8m

1.5m

2.3m

3.1m

4.6m

۷

0.8m

1.5m

2.3m

3.8m

4.5m

V Spread : 21.4m

H Spread : 21.8m

