landscape



LRIO | oslo

14W LED



ACCENT LIGHT ZJ14 :

The ZJ14 landscape fixture is perfect for spot lighting applications in any outdoor project. Achieve beautiful color changing effects on building facades, trees, sculptures, and other architectural elements. RGB and RGBW options with internal DMX for easy integration with IFX Spectrum Select systems.

- 5-year warranty
- Long life : 50,000 hours

PHOTOMETRICS

14W-

| К | | | | |
|------------|---------------|--------|--------|---------|
| 120 H(m) | D (m) | MaxLux | MedLux | - 🛱 |
| 90 0.6 | 0 0,31 | 3415 | 2013 | Λ |
| 7 13 1.2 | 0 0,63 | 854 | 503 | |
| 60 14 | 0 0,94 | 379 | 224 | |
| 45 2.4 | 0 1.25 | 213 | 126 | |
| cd/mgm 3.0 | 0 1,57 | 137 | 81 | |

ORDERING GUIDE

example product code: JZ14/2D/FL45/RGBW/BL/SPK

| | SERIES | WATTAGE | INPUT VOLTAGE* | BEAM SPREAD** | COLOR TEMP | FINISH | MOUNTING |
|-------------------|--------|---------|-------------------|------------------|---------------|--|------------------|
| | JZ | 14 | 2D | FL45 | RGBW | BL | SPK |
| | | | 2D -24VDC | SP20-20° | RGBW | BL —Black | SPK—Stake Mount |
| | | | 1A-12VAC | SP24-24° | RGB | S—Silver | SM—Surface Mount |
| | | | SP30-30° | 830-3000K | BS-Brass | | |
| | | | SP36-36° | | | | |
| | | | FL45 -45° | | | | |
| illumin <i>fx</i> | | | | FL60-60° | | | |
| | | | | | | serves the right to ns at any time with | • |

SPECIFICATIONS

| Housing | Machined aluminum 6063 | | | |
|-----------------|------------------------------------|---------------|--|--|
| LED | COB / RGB or RGBW | | | |
| Lumens | ~70 lumens/watt | | | |
| Boom Corood | Single Color | 24 / 36 / 60° | | |
| Beam Spread | RGB / RGBW | 20 / 30 / 45° | | |
| Lens | Efficiency ≥85% | | | |
| Cable Gland | IP68 PG-9 PVC | | | |
| Waterproof Seal | Molded shaped double silicone seal | | | |
| Cable | 1 meter | | | |
| | | | | |

DIMENSIONS

