

RIO | oslo

MANTA RAY

6W LED

MR4



STAND-MR4 optional tripod stand







MANTA RAY MR4:

The MANTA RAY MR4 underwater fixture is a low profile spot light waterproof fixture. Its slim design makes it a perfect choice for smaller underwater jobs. Though it comes in a small package, this LED fixture puts out a lot of light output, and is very easy to install. Use the optional tripod stand (STAND-MR4) for more installation flexibility.

- 5-year warranty
- Long life: 50,000 hours
- NOTE: MUST BE INSTALLED UNDERWATER to prevent light from overheating

LED Array

3 x 2W

3 x 2W

3 x 2W


PHOTOMETRICS

Model Number

MR4-L32-1AWA-S-20HW

MR4-L32-1ACA-S-20HW

MR4-L32-2DXB-S-201M





Input

Voltage

12VAC

12VAC

24VDC

| 1100 | C45(Max): C0/C180: C90/C270: | = |
|------|------------------------------------|---|
| | 000 | |
| | | |

Color

Warm White

3000K

Cool White

6000K

RGB

| Beam Angle | Cord Termination | Max Power | LUM Flux |
|---------------|---------------------|--------------|-------------|
| 15° | 2-wire | 5.8W | 272 |
| 15° | 2-wire | 5.8W | 321 |
| | Male QC Plug | 7.7W | Variable |

2.5

.45

SPECIFICATIONS

| Housing & Bracket | 316# stainless steel | |
|-------------------|--|--|
| Front Cover | 316L# stainless steel | |
| Glass | Step-tempered clear glass T=5mm | |
| Cable Gland | IP68 PG-11 copper and nickel coated | |
| Waterproof Seal | Molded shaped silicon seal under front cover Silicon glue encasing LEDs, lens and PCB | |
| PCB | Coefficient of heat conductivity>2.0w/mk | |
| Lens | Optical lens efficiency ≥85% | |
| Driver | Single color—1 circuit RGB 3in1—3 circuits | |
| Cord | 20 ft | |
| Cord Termination | OSLO WHITE—Tinned wire ends RIO RGB—Male IP68 Quick-Connect | |
| Environment | Water temperature : -4°~104°F Less than 1 meter depth | |

DIMENSIONS

