landscape

KR










TS-1 optional tree strap

The KIM 10/15 watt line voltage landscape stake fixture is a high powered LED solution for almost any outdoor landscape lighting project. Use it to light up building facades, trees, retaining walls, and columns. Installation is quick and easy and the COB LED provides amazingly high lumen output from a small energy efficient lighting fixture.

- 5-year warranty
- Long life : 30,000 hours

PHOTOMETRICS



ORDERING GUIDE

example product code: KR15/A/SP15/UA/830/DG

| SERIES | TYPE | BEAM SPREAD | INPUT VOLTAGE | CRI | COLOR TEMP | FINISH |
|------------------|-------------------------|------------------------------|------------------|-----|------------------|----------------------|
| KR15 | А | SP15 | UA | 8 | 30 | DG |
| KR10-10W | A —Angled Shroud | SP15—15° very narrow spot | | | 57-5700K | DG —Dark Grey |
| KR15 -15W | S—Straight Shroud | SP25—25° spot | | | 30 —3000K | BL—Black |
| | | SP38—38° spot | | | | WH-White |
| | | FL60—60° flood | | | | |

E(fc)

1.5

2.5

5.0

10

38



oslo

KIM

10/15W COB LED

SPECIFICATIONS

| Housing | Die cast aluminum alloy | | | |
|---------------|--------------------------|----------------------------|--|--|
| Gasket | Silicon rubber ring | | | |
| Glass | Tempered Glass | | | |
| Reflector | High purity aluminum | | | |
| PCB Material | Aluminum | | | |
| Driver | Constant current COB LED | | | |
| Input Voltage | 120~277VAC | | | |
| Ambient Temp | -4°F~113°F | | | |
| Color Temp | 3000 / 5700K | | | |
| Beam Angle | 15° / 25° / 38° / 60° | | | |
| | 4000 | 3000K - 550 lm / CRI > 80 | | |
| | 10W | 5700K - 850 lm / CRI > 80 | | |
| Lumens / CRI | 4534 | 3000K - 1080 lm / CRI > 80 | | |
| | 15W | 5700K - 1380 lm / CRI > 80 | | |
| | | | | |

DIMENSIONS

