











IMFLEX SFT:

SlimFlex IP68 RGBW is the ultimate in flexible waterproof color changing lighting. Strong, vibrant whites, along with 16.8 million additional color comminations make this a can't miss solution. Our 2.5" cutting intervals help to fill any gaps at corners, and spillways with light. This product is cuttable in the field, but not re-connectable.

- Long life LED
- 2 year warranty
- Custom lengths available by special order


SPECIFICATIONS

| Housing | IP68—Filled Molded silicon sleeve | | |
|----------------------|-----------------------------------|--|--|
| Voltage | RGBW—24V DC | | |
| Length | 5m [16.4'] per reel | | |
| Cuttable | RGBW—Every ~2.5" | | |
| Power | RGBW—72 W [14.4W/m] | | |
| Max Connection | 10m [32.8'] (2 reels) | | |
| Current | 24v —600mA/m | | |
| Humidity | 90% RH | | |
| Ambient Temp | -40°F ~ 140°F | | |
| CRI | >Ra94+ (6000K) | | |
| Min. Buckling Radius | >50mm | | |

ACCESSORIES (per reel)

| End Cap | 5 | Ø |
|---------------|----|----------|
| Mounting Clip | 15 | C |

DIMENSIONS



| Model Number | Current | Watts/m | Color | Total Watts | Cord Termination | LUM Flux/m | IP Rating |
|---------------------|------------|---------|-------|----------------|---------------------|---------------|-----------|
| SFT35-96-2-RGBW6-68 | 0.6 amps/m | 14.4W/m | RGBW | 72W | 5-wire | 1250LM | 68 |

